



## ORDERING CODES RMF Systems

### Contamination Monitoring System



Table 1	Table 2	Table 3	Table 4	Table 5	Table 6
CMS					

**Table 1** Basic configuration

CMS	In-line Contamination Monitoring System	
-----	---	--

**Table 2** Sensor option

W	Water sensor option, adds the facility to measure water content and fluid temperature	Mineral oil only
0	No water sensor	

**Table 3** Fluid Compatibility

M	Mineral Fluid Compatibility
---	-----------------------------

**Table 4** Key board /display

K	Adds 6 key keypad and 128 x 64 pixel back lit graphical display	Standard
0	No keypad and display	

**Table 5** Relays

R	Adds two fully customisable "alarm" relay outputs to set upper and lower limits for the test results and indicates these via a "multicolour" front panel LED indicator and/or remote devices.
---	---

**Table 6** Port Options

G1	Test point M16 x 2	Standard
G2	1/8" BSP	
G3	1/4" BSP	

**Optional** Related products (to be ordered separately)

CMS-RDU	CMS remote display unit with keypad	Same port size as CMS unit (see table 4)
CMS-USBi	CMS to PC USB connector unit	

#### Warranty and Recalibration

The CMS is guaranteed for 12 months from date of receipt and is recommended to be recalibrated every 12 months. Return to RMF Systems for recalibration.