



ORDERING CODES RMF Systems

OQS - Oil Quality Sensor

Table 1	Table 2	Table 3	Table 4	Table 5	Table 6
OQS					

Table 1 Basic configuration

OQS	Oil QualitySensor
-----	-------------------

Table 2 Material case

1	Stainless steel	Standard
---	-----------------	----------

Table 3 Threaded connection options

06	G3/8" BSP male thread	
08	G1/2" BSP male thread	Standard
M12	M12x1,5 metric thread	
M16	M16x1,5 metric thread	
M18	M18x1,5 metric thread	
M20	M20x1,5 metric thread	
M22	M22x1,5 metric thread	
	Alternative connections on request	

Table 4 Sealing / washer options

0	Dowty seal	Buna	Standard
1	Dowty seal	Viton	

Table 5 Output connection options

SC	Straight circular connector	Lumberg M16x0,75 (6-pin IP68)	Standard
AC	Right angle circular connector	Lumberg M16x0,75 (6-pin IP68)	
FL2	Flying leads with 2mtr of cable		Other lenghts available on request
	Various cable lengths can be accommodated with mating connector (on request)		

Table 6 Communications options

1	RS232 (4-20mA)	Standard
2	RS482 (Modbus)	
3	CANbus	

Ordering code of our standard /default unit:

OQS-1-08-0-SC-1
OIL QUALITY SENSOR/ 1/2"BSP/ BUNA/ RS232 & 4-20MA